

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
11 March 2004 (11.03.2004)


PCT

(10) International Publication Number
WO 2004/021336 A2

- (51) International Patent Classification⁷: G11B 7/00 F. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (21) International Application Number: PCT/TB2003/003760 (74) Agent: DEGUELLE, Wilhelmus, H., G.; Philips Intellectual Property & Standards, Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (22) International Filing Date: 14 August 2003 (14.08.2003)
- (25) Filing Language: English (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (26) Publication Language: English
- (30) Priority Data: 02078573.9 29 August 2002 (29.08.2002) EP (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- (71) Applicant (*for all designated States except US*): KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (*for US only*): VAN DEN OETELAAR, Ronald, J., A. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). MARTENS, Hubert, C.,

[Continued on next page]

(54) Title: MULTI-STACK OPTICAL DATA STORAGE MEDIUM AND USE OF SUCH MEDIUM



(57) Abstract: A multi-stack optical data storage medium (30) for recording using a focused radiation beam (40) having a wavelength λ and entering through an entrance face (41) of the medium (30) is described. It has a first substrate (31a) with present on a side thereof a first recording stack (33) named L0, comprising a recordable type L0 recording layer (35), and formed in a first L0 guide groove (38). The L0 recording layer (35) has a thickness $dL0G$ in the groove (38) and a thickness $dL0L$ adjacent the groove (38). A second substrate (31b) has present on a side thereof a second recording stack (32) named L1 comprising a recordable type L1 recording layer (34). The L1 recording layer has a thickness $dL1G$ in the groove and a thickness $dL1L$ adjacent the groove. The second recording stack (32) is present at a position closer to the entrance face (41) than the L0 recording stack (33) and is formed in a second L1 guide groove (37). The depth of the first L0 guide groove (38) is smaller than 0.15λ and $dL0L$ is substantially equal to or larger than $dL1G$ by which it is achieved that the L0 stack (33) has a reflection level and a modulation level of recorded marks compatible with the dual layer DVD-ROM specification.